



# CORREVIT® S-HR

## Non-Contact Optical High-Resolution Sensor

for

### slip-free measurement of longitudinal and transversal dynamics

- Accuracy of the unfiltered angle within the range of  $\pm 15^\circ = 0.1^\circ$
- High-resolution slip angle measurement by enhanced measuring principle
- Working range of  $250 \pm 50$  mm from test surface
- Applicable from 0.5 kph ... 250 kph\*
- Adjustable filter time for speed signal and angle up from  $\pm 15^\circ$  (unfiltered, moving average 8 ... 512 ms)  
FIR Filter with constant filter time (adjustable)

Considerably improved performance enabled by the application of the latest technologies:

- ⇒ Latest halogen lamp with aluminum reflector
  - ⇒ Improved distance linearity
  - ⇒ Easier mounting
  - ⇒ Improved signal processing by ideal combination of analog and digital signal conditioning (DSP-FPGA technology)
  - ⇒ Reduced noise in output signal
  - ⇒ Improved measurement features on various surfaces
  - ⇒ Improved standstill indication
  - ⇒ Quick filter start-up
- Extremely high measuring accuracy\*\* better than  $\pm 0.1\%$  as a result of precise optics and digital signal processing
  - Programmable standard analog and digital signal outputs
  - All measured values available in all output formats
  - Direct connection to PC and virtually all data acquisition systems
- Signal outputs:     Analog  $\pm 10V$  / 16 Bit  
                          Digitale Pulse  
                          CAN-Bus  
                          RS232  
                          USB
- No extensive initialization required
  - Negligible service and maintenance requirements as a result of durable technology
  - Tested and used under extreme environmental conditions



\* high-resolution angle output up from 10 kph / \*\* with calibration on the test surface

## Typical Technical Data

### Performance specifications

Angle measurement range:	±40°
High-Resolution:	±15°
Speed range*:	0.5 ... 250 kph
Distance resolution:	2.66 mm
Distance measurement deviation**:	<±0.1%
High-resolution angle output range:	10 ... 250 km/h
Angle resolution:	0.01°
Angle accuracy:	0.1°
Angle resolution (-40°...-15°; +15°...+40°):	0.1°
Measurement frequency:	250 Hz
Working distance and range:	250 ±50 mm

### Signal outputs

Digital output 1 - IVI or V <sub>L</sub> ***:	1 ... 1000 pulses/m
Digital output 2 - V <sub>q</sub> or angle***:	f <sub>center</sub> = 5 kHz
Analog output 1 - IVI or V <sub>L</sub> ***:	0 ... 10 V
Analog output 2 - V <sub>q</sub> :	-10 ... +10 V
Analog output 3 - angle:	-10 ... +10 V

### Signal inputs

Trigger input:	for calibration with LB / Brake switch
Analog input 1+2:	-10 ... +10 V
Counter input:	0 ... 100 KHz

### Interfaces:

analog ±10V / 16 Bit  
 digital pulses  
 CAN 2.0B  
 RS232  
 USB 2.0 Full Speed

### System specifications

Power supply:	10 ... 28 V, 60W
Temperature range: Operation:	- 25 ... +60 °C
Storage:	- 10 ... +85 °C
Rel. humidity:	5 ... 80% non condensing
Protection standard sensor head (cable mounted):	IP 67
Protection standard electronics:	IP 50
Dimensions of the sensor head (l x w x h):	165 x 50 x 130 mm
Weight of the sensor head:	1250 g ****
Dimensions of the electronics (l x w x h):	164 x 125 x 95 mm
Weight of the electronics:	600 g
Illumination:	2 x 20 W Halogen (Aluline Pro)
Splash guard:	yes
Sensor cable:	5 m

\* optional: calibrated up to 400 km/h  
 \*\* with calibration on test surface

\*\*\* switching-over between the respective measured variables  
 via CeCalWin Pro possible

\*\*\*\* optional: sensor head made of magnesium = approx. 900 g

© CORRSYS-DATRON Sensorsysteme GmbH, Germany

S-HR\_d-075-e-rev004 03/09 CORREVIT® is a registered trademark of CORRSYS-DATRON Sensorsysteme GmbH



In a continuous effort to improve our products, CORRSYS-DATRON reserves the right to change specifications without prior notice.

**CORRSYS-DATRON**  
 www.corrsys-datron.com

#### International Headquarters

CORRSYS-DATRON Sensorsysteme GmbH  
 P.O. Box 1349 • 35523 Wetzlar / Germany  
 Phone: +49-6441-9282-0  
 Fax: +49-6441-9282-17  
 e-mail: sales@corrsys-datron.com

#### North American Headquarters

CORRSYS-DATRON Sensorsystems Inc.  
 40000 Grand River, Suite 503 • Novi, MI 48375 • USA  
 Phone: 248-615-2035 • Toll-free: 800-832-0732  
 Fax: 248-615-2184  
 e-mail: USA-sales@corrsys-datron.com

#### Chinese Headquarters

CORRSYS-DATRON Sensorsysteme GmbH - China  
 Room 610, JinTianDi International Mansion,  
 No. 998 RenMin Road, Shanghai (200021), P.R.China  
 Phone: ++86-21-63114144 • Fax: ++86-21-63114154  
 e-mail: Xiaoying.Li@corrsys-datron.com.cn